Application No. 10/575,777 Docket No.: 0599-0215PUSI
Amendment dated December 12, 2008

## AMENDMENTS TO THE CLAIMS

(Currently Amended) A laminated film, comprising 5 or more laminated resin layers; the
thickness of each of the resin layers being from 1 to 100 nm; and the film having a layer
structure wherein the thicknesses of resin layers having the same composition A; of the resin
layers; increase or decrease from the side of a surface of the laminated film toward the side of the
other surface opposite thereto and wherein the maximum light ray reflectivity is 25% or less in a
wavelength range of 400 to 2500 nm.

- 2. (Currently Amended) The laminated film according to claim 1, comprising the resin layers having of the composition A, and the resin layers having a composition B—of the resin layers; and having a layer structure wherein the thickness ratio between the resin layer having the composition A and the resin layer having the composition B which are adjacent to each other increases or decreases from the side of the surface of the laminated film toward the side of the other surface opposite thereto.
- 3. (Currently Amended) The laminated film according to claim 1, comprising the resin layers having of the composition A, and the-resin layers having a composition B-of the resin layers; and having a layer structure wherein the thicknesses of the resin layers having the composition A increase from the side of the surface of the laminated film toward the side of the other surface opposite thereto, and thicknesses of the resin layers having the composition B decrease from the side of the surface of the laminated film toward the side of the other surface opposite thereto.
- 4. (Currently Amended) The laminated film according to claim 1, having a layer structure wherein the thicknesses of the resin layers having the composition A increase from the first surface towards the center and then decrease from the center to the other surface or decrease from the first surface toward the center and then increase from the center to the other surface or decrease from the cide of the surface of the laminated film toward the center in the layer-

Amendment dated December 12, 2008

laminated direction, and the thicknesses also increase or decrease from the side of the other surface toward the center in the layer laminated direction.

- 5 (Previously Presented) The laminated film according to claim 1, comprising two thermoplastic resins having a refractive index difference of 0.05 or more.
- 6. (Previously Presented) The laminated film according to claim 1, wherein the thickness of each of a half or more of the layers constituting the laminated film is 30 nm or less.
- 7. (Currently Amended) The laminated film according to any one of claims 1 to 4 claim 1, comprising a pair of adjacent ones of the resin layers wherein the ratio between the thicknesses of the adjacent layers (the thickness of the thin layer/that layer to that of the thick layer) is 0.8 or more and 1.0 or less, and a pair of adjacent ones of the resin layers wherein the ratio between the thicknesses of the adjacent layers is 0.01 or more and 0.5 or less.
- 8. (Previously Presented) The laminated film according to claim 1, wherein the number of the laminated layers is 50 or more.
- 9. (Cancelled)
- (Previously Presented) The laminated film according to claim 2, comprising two 10. thermoplastic resins having a refractive index difference of 0.05 or more.
- 11 (Previously Presented) The laminated film according to claim 3, comprising two thermoplastic resins having a refractive index difference of 0.05 or more.
- (Previously Presented) The laminated film according to claim 4, comprising two 12. thermoplastic resins having a refractive index difference of 0.05 or more.

Application No. 10/575,777 Docket No : 0599-0215PUS1

13. (Previously Presented) The laminated film according to claim 2, wherein the thickness of each of a half or more of the layers constituting the laminated film is 30 nm or less.

- 14 (Previously Presented) The laminated film according to claim 3, wherein the thickness of each of a half or more of the layers constituting the laminated film is 30 nm or less.
- 15. (Previously Presented) The laminated film according to claim 4, wherein the thickness of each of a half or more of the layers constituting the laminated film is 30 nm or less.
- 16. (Currently Amended) The laminated film according to claim 2, comprising a pair of adjacent ones of the resin layers wherein the ratio between the thicknesses of the adjacent layers (the thickness of the thin layer/that layer to that of the thick layer) is 0.8 or more and 1.0 or less. and a pair of adjacent ones of the resin layers wherein the ratio between the thicknesses of the adjacent layers is 0.01 or more and 0.5 or less.
- 17. (Currently Amended) The laminated film according to claim 3, comprising a pair of adjacent ones of the resin layers wherein the ratio between the thicknesses of the adjacent layers (the thickness of the thin laver/that laver to that of the thick laver) is 0.8 or more and 1.0 or less. and a pair of adjacent ones of the resin layers wherein the ratio between the thicknesses of the adjacent layers is 0.01 or more and 0.5 or less.
- 18. (Currently Amended) The laminated film according to claim 4, comprising a pair of adjacent ones of the resin layers wherein the ratio between the thicknesses of the adjacent layers (the thickness of the thin layer/that layer to that of the thick layer) is 0.8 or more and 1.0 or less, and a pair of adjacent ones of the resin layers wherein the ratio between the thicknesses of the adjacent layers is 0.01 or more and 0.5 or less.

19. - 20. (Cancelled)